




COLLECTION • ILLUSION


TUFT STRUCTURÉ • STRUCTURED LOOP PILE

ILLUSION

135620505-00xxx



00113




00123




00130




00131




00153




00230



00231




00239



00300



00302




00303




00471




00479



00592



00593



SITE CERTIFIÉ



Répond à la démarche

HQE

LEED

M1



0679-CPR-0196
07
EN 14041 : 2004

Bfl-s1 / Bfl-s1

Classification 33 / Classification 33

Envers vnyil 100 % recyclés / 100 % recycled vnyil backing

Stabilité dimensionnelle / Dimensional stability

Produit teinté dans la masse / Solution dyed product

100 % Polyamide / 100 % Polyamide

ILLUSION

SPÉCIFICATION

Composition fibreuse 100% Polyamide
(Teint masse)

Jauge 5/64 loop pile

Densité 213 200 Stitches/m²

Poids de fil 750 g/m²

Masse de velours utile 370 g/m²

Epaisseur velours utile 2.9 mm

Densité du velours de surface 0,128 g/cm³

Masse totale 4419 g/m²

Epaisseur totale 6.8 mm

Premier dossier Non tissé

Envers Matière 100% recyclé

Dimensions 50x50cm

Dalles par boîte 20 = 5m²

PERFORMANCES TECHNIQUES

Stabilité dimensionnelle ≤ 0,10%

Comportement au feu Bfls1

Bruits de choc ΔL (w) 24 dB

Absorption acoustique α_w = 0,15 (H)

Résistance électrique ≤ 2,0kV RT ~ 10¹⁰Ω

Résistance thermique 0,09 m² K/W

Solidité à la lumière 7/8

Aptitude chaise à roulette R≥2,4

Classement européen 33

SENS DE POSE



SPECIFICATION

Pile fiber 100% Polyamide

(Solution dyed)

Gauge 5/64 loop pile

Tuft density 178 235 Stitches/sqy²

Total pile mass 21.5 oz/sqy

Pile weight of wear layer 10.9 oz/sqy

Pile height 0.11 in

Surface pile density 0.0739 oz/in³

Total weight 103.3 oz/sqy

Total Thickness 0.27 in

Primary backing No woven

Backing 100% recycled PVC

Tile size 19.68x19.68in

Tiles per box 20 = 5.97 sqy

TECHNICAL PERFORMANCES

Dimensional stability ≤ 0,10%

Reaction to fire Bfls1

Impact sound reduction ΔL (w) 24 dB

Sound absorption α_w = 0,15 (H)

Electrostatic properties ≤ 2,0kV RT ~ 10¹⁰Ω

Thermal resistance 0,09m² K/W

Light fastness 7/8

Castor chair R≥2,4

European classification 33


INSTALLATION



Classification

Luxury class

33 (4)	32 (3)	31 (2+)	LC1	LC2	LC3	LC4	LC5	
heavy	general	moderate	simple	good	high	luxurious	prestige	



Description
Backing System
Vinyl Backing reinforced with
glass fibre / 100% recycled PVC backing



Description - Loop pile / Bouclé
100% Polyamide
Teint masse / Solution dyed



SITE CERTIFIÉ

Répond à la démarche

HQE

LEED

