



DATA SHEET

Gecko

issue 3/21

Entrance Carpet Tiles

pg ½

Distributor/Manufacturer

Advance Flooring Systems Limited/Voxflor

Trade Name

Gecko

Product Description

Solution Dyed nylon 6 entrance carpet tiles with a Declare certified Comfort Back or PVC backing system.

Product Benefit

Gecko is a sustainably manufactured entrance carpet tile with thick denier fibres designed to trap soil from any direction, that is durable and easy to clean.

Area of Application

Gecko is suitable for building entrances and for use in any high traffic commercial areas.

Composition

Gecko carpet tiles are made with a tufted loop pile construction consisting of 100% Universal nylon 6 bonded to Declare Certified Comfort Back or PVC backing system.

Dimensions

Overall thickness	6.6mm (PVC), 10mm (Comfort-Backed)
Tile size	500 x 500mm

Pattern & Colours

Tufted level loop appearance available in 1 colour

Manufacture

Gecko carpet tiles are manufactured in China, by Voxflor using manufacturing processes that are ISO 14001:2004 compliant for its Environmental Management Systems.

Smoke/Fire

Gecko entrance carpet tiles have been tested and exceed the NZ requirements.

Antistatic

Gecko entrance carpet tiles have been tested to have an electrostatic resistance of $\geq 10^9 \Omega$.

Durability

Class 33, Heavy Commercial

Advance Flooring Systems Ltd

email: info@advanceflooringsystems.com

www.advanceflooringsystems.com

Call us: **0508 238 262**


Advance
FLOORING SYSTEMS



DATA SHEET

Gecko

issue 03/21

Entrance Carpet Tiles

pg 2/2

Sound Absorption

Gecko carpet tiles can reduce impact noise by up to 21 dB.

UV Resistance

Some fading may be observed in areas of intense sunlight.


Sustainability

Voxflor is committed to the protection of the environment and all products are manufactured to strict ISO 14001: 2004 standards.

Installation

Gecko carpet tiles must be installed by a competent and experienced carpet installer and we recommend the full stick method - more information on the recommended installation procedures is available on our website www.advanceflooringsystems.com or upon request.

We recommend the following installation method for Gecko.



QUARTER-TURN

Recommended Adhesives

Entrance matting applications - Giltgrip 88 – Gilt Edge Industries Ltd

Applications other than entrance matting - Strongbond 65 – Look Floors, or Polymer 999 PS – Gilt Edge Industries Ltd.

Cleaning and Maintenance

Proper maintenance is one of the most important factors to ensure good performance of any carpet.

Gecko should be vacuumed daily as it will collect up to 90% soiling before it is tracked into the interior of the building. More information on the recommended maintenance procedures is available on our website www.advanceflooringsystems.com or upon request.

Warranty

The manufacturer provides a 10-year limited warranty.

Advance Flooring Systems Ltd

email: info@advanceflooringsystems.com

www.advanceflooringsystems.com

Call us: **0508 238 262**



Advance
FLOORING SYSTEMS