

## Advance Flooring Entrance Matting Systems with Polyamide Inserts Advance Flooring Systems

Final Assembly: Wiri, Auckland, New Zealand

Life Expectancy: 15 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety, Take Back Program (Wiri, Auckland, New Zealand), Recyclable (66%),

Landfill (34%)

## Ingredients:

**Aluminium:** Aluminum; Boron; Chromium, metallic; Copper; Iron; Magnesium; Manganese; Nickel (Metallic); Silicon; Titanium; Zinc; **Zeno:** Vinyl chloride-vinyl acetate copolymers; Nylon 6; Calcium Carbonate; n-Alkane(C10-21)sulfonic acid phenyl ester; Aluminum hydroxide; Ethanol, 2,2'-oxybis-, dibenzoate; Polyethylene Terephthalate; Unnamed Substance (0.388-0.482%)<sup>1</sup>; Propanol, oxybis-, dibenzoate; Calcium Oxide; **Matfoot:** Thermoplastic Polymer; 1-Propene, polymer with ethene; **Joiner:** Silica gel, pptd., cryst.-free; Tin chloride (SnCl2); Carbon black; Zinc oxide; **Tape S411V2:** Unnamed Substance (0.11-0.27%)<sup>1</sup>; **Glue:** 2-Propenoic acid, 2-cyano-, ethyl ester

<sup>1</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

## I-13 Red List:

□ LBC Red List Free

■ LBC Red List Approved

Declared

% Disclosed: 99.25% at 100ppm VOC Content: Not Applicable

I-10 Interior Performance: Not Applicable
I-14 Responsible Sourcing: Not Applicable

AFS-0001 EXP. 01 MAY 2022 Original Issue Date: 2021