



	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
PRODUCT DESCRIPTION				
Surface treatment	-	-	-	-
Surface complex	-	-	-	-
Foam	-	-	-	-
Thickness	EN 428	-	mm	1,65
Weight	EN 430	-	kg/m ²	1,35
Length	EN 426	-	lm	45 standard
Width	EN 426	-	lm	2
SPORT PROPERTIES				
Shock absorption	EN 14808	≥ 25	%	-
Vertical deformation	EN 14809	≤ 3.5	mm	-
Energy return	NF P 90 203	≥ 0.31	m/s	-
Sliding coefficient	EN 13036-4	80 to 110	-	-
Ball bounce	EN 12235	≥ 90	%	-
Ball speed	UEFA	50 to 65	cm	-
	ITF	-	-	-
TECHNICAL CHARACTERISTICS				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	-
Impact resistance	EN 1517	≥ 8	N/m	-
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
CLASSIFICATION				
Fire	EN 13501-1	-	-	
Treatment	-	-	-	-
DECLARATION OF PERFORMANCE				
	DOP n°xxx	-	-	Fire
INSTALLATION METHODS				
	Gerflor's recommendation		Unit	Results
Loose lay installation on the subfloor before "flexible" installation of a sports flooring method on it	-	-	-	RH <80% (BS8203) or <7.0% humidity (CCM)
COLOUR RANGE				
-				

