

Technical Data Sheet | Create BLOQ Carpet Tiles

Product Name: Create SMALL, MEDIUM, LARGE

Dimensions: 500 x 500mm

Total Thickness: 8.5mm (ISO 1765)

Density: 0.126 g/m³ (ISO 8543)

Packaging: Box = 16 tiles / 4m²

Pallet = 160m²



Type of manufacturer: ISO 2424

Tufted Patterened Loop Pile 1/10"

Pile Fibre Composition: ISO 2424

100% Polyamide 6
Solution Dyed Nylon made by Aquafil

Secondary Backing: ISO 2424

Bitback, Modified Bitumen
70% Recycled Content

Pile Weight: ISO 8543

1000 g/m²

Surface Pile Weight: ISO 8543

590 g/m²

Total Weight: ISO 8543

5000 g/m²

Pile Height: ISO 1766

4.6 mm

Number of tufts: ISO 1763

215 000 /m²

Dimensional Stability: ISO 2551

≤ 0.2%

Classification: EN 1307

33

Luxury Rating: EN 1307

LC2

Castor Chair Rating: EN 985

A: Intensive use

Fire Classification: EN 13501-1

Bfl-s1

Impact sound Insulation: EN ISO 10140-3

ΔL_w : 26 dB

Sound Absorbtion: EN ISO 354

Frequency Hz	125	250	500	1000	2000	4000
a_s	0.01	0.03	0.10	0.22	0.36	0.46

Noise Reduction: EN ISO 354

a_w : 0.20

Permanent Antistatic: ISO 6356

≤ 2 kV

Transversial Resistance: ISO 8302

0.079 m² K/W

Technical Data Sheet | Create BLOQ Carpet Tiles



Thermal Resistance: ISO 10965

$\leq 1 \times 10^9$ Ohm

Colour Fastness to Light: EN ISO 105-B02

≥ 7

Colour Fastness to Water: EN ISO 105-E01
 $\leq 0.2\%$

Rubbing Fastness: EN ISO 105-X12

≥ 4

Number of colours: 13 Colours

Large: 6 | Medium: 1 | Small: 6



in progress

EN 14041

DOP: 1137-127659

NB: 2401

20



For use as floor covering in buildings.

BLOQ
De Blokmat 29
NL - 8281 JH Genemuiden