

Technical Data Sheet

AKOplus - 1/23



Manufacturer/Distributor

Advance Flooring Systems Ltd

Trade Names

AKOplus Safety mat

Product Description

PVC foam-coated glass fibre yarn with a PVC granulate surface.

Particular Benefit

Long lasting highly slip resistant matting, suitable for use in slippery or icy environments.

Area of Application

Ideal for use in both interior and exterior locations needing anti-slip and antifatigue matting. As anti-slip sound absorbent matting in accessways of factories, offices, homes, schools, on paths, passages, ramps and stairs.

Composition

PES/ Glass fibre yarn coated on both sides with proprietary PVC foam having PVC granulate bonded on top surface of mat. Weight 2000gsm.

Dimensions

Roll Width: 900mm, 1200mm, 1800mm

Length: 10m

Thickness: 6-7mm

AKOplus Safety mat can be cut to client specification without fraying.

Colour

Black

Manufacture

AKOplus is manufactured in Germany by Kolckmann GmbH

UV Resistance

Classified as UV resistant, however some shade variation may become apparent in UV intense locations.

Technical Data Sheet

AKOplus - 1/23



Moisture Behaviour

Water resistant – not affected by warm or cold conditions.

Safety

High slip resistant even in wet or icy conditions.

Installation

Mats are self-securing over 3sqm or can be secured with screws, washers, staples or carpet bars. Please refer to Installation Guidelines

Cleaning and Maintenance

Easily cleaned with vacuum cleaner or pressure washer. Avoid high water pressure.

Guarantee

Guaranteed for 1 year against premature failure due to manufacturing defects.

Supply

Advance Flooring Systems Ltd has a national network of matting consultants and distributors. Please phone Advance for details of those in your area – toll free 0508 ADVANCE (0508 238 262).