

# **CORAL SEA COLLECTION**

## **Technical Specifications**

Construction: Multi-level Loop

Fiber: Voxflor® Certified Nylon

**Gauge:** 1/12"

Stitches: 10 per inch

Area per carton: 6m<sup>2</sup>

**Traffic Classification:** Commercial - Heavy Duty

Average Pile Height: 4.0 ± 0.5 mm

Standard Backing: EcoAce-Bac®

Tile Size: 50 x 50 cm


Pile Weight: 20 OZ/yd<sup>2</sup>

Total Thickness: 6.5 ± 0.5 mm

Piece per carton: 24 pieces

Anti-microbial: Ultra Fresh (Available)

#### **Installation Methods**







\*\*These given methods of installation are considered as

However, certain cases and needs may be different, and designs will differ accordingly.

## **Certifications**























DOWNLOAD

**Certificate Of CRI** 



# **Performance Specifications**

	Test Code	Standard	Test Result
Flammability Tests			
Radiant Panel	ASTM E 648	≥.45 watt/cm²	Class I
Methenamine Pill	ASTM D2859	7 out of 8	8
Smoke Density	ASTM E 662	≤ 450 DMC	≤ 450
Stability			
Delamination	ASTM D3936	≥ 3.0 lbc/in	No Separation
Dimensional Stability	AACHEN	≤ 0.2%	≤ 0.2%
Tuft Bind	ASTM D1335	≥ 8.0 lbs	≥ 8.0 lbs
Anti-Static			
Static Propensity	AATCC 134	≤ 3.5 kV	≤ 3.5 kV
Colour Fastness			
Light	AATCC 16 E	≥ 4-5	4-5
Rubbing/Crocking	AATCC 165	≥ 4-5	4-5
Wear Tests			
Castor Chair	BS EN 985	r ≥ 2.4	r = 2.8
Hexapod Drum	ASTM D5252	≥ 3-4	3
Generic Tests			
Nylon Carpet with EcoAce-Bac®	GLP No.: 100231		Accredited
Acoustic-Nylon	BS EN ISO 354	Absorption Coefficient-NRC	aw =0.15(H)

## Warranty

15-year Commercial Limited Warranty

DOWNLOAD

#### **Additional Information**

- VOXFLOR uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more

## **Additional Files**

**Installation Guidelines** 

**DOWNLOAD** 

**Maintenance Guidelines DOWNLOAD** 





Declare.

