

Advance Flooring Entrance Matting Systems with Polyamide Inserts Advance Flooring Systems

Final Assembly: Wiri, Auckland, New Zealand

Life Expectancy: 15 Year(s)

End of Life Options: Salvageable/Reusable in its Entirety, Take Back Program (Wiri, Auckland, New Zealand), Recyclable (66%),

Landfill (34%)

Ingredients:

Aluminium: Aluminum; Boron; Chromium, metallic; Copper; Iron; Magnesium; Manganese; Nickel (Metallic); Silicon; Titanium; Zinc; **Symphony 2:** Calcium Carbonate; Nylon 6; Zeolites other than erionite (clinoptilolite, phillipsite,mordenite, non-fibrous Japanese zeolite, synthetic zeolites); **Matfoot:** Thermoplastic Polymer; 1-Propene, polymer with ethene; **Joiner:** Silica gel, pptd., cryst.-free; Tin chloride (SnCl2); Carbon black; Zinc oxide; **Tape S411V2:** Unnamed Substance (0.11-0.27%)¹; **Glue:** 2-

Propenoic acid, 2-cyano-, ethyl ester

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

☐ LBC Red List Free

% Disclosed: 99.73% at 100ppm VOC Content: Not Applicable

■ LBC Red List Approved

□ Declared

I-10 Interior Performance: Not Applicable I-14 Responsible Sourcing: Not Applicable

AFS-0001 EXP. 01 MAY 2025 Original Issue Date: 2021