# Product Review tretford Roll, Tile and Custom Rugs 05/24

pg 1/4





## Product Review tretford Roll, Tile and Custom Rugs 05/24

pg 2/4

#### **Product class**

Class 1 - Batch or mass-produced products

#### **Product name**

tretford - Roll, Tile and Custom Rugs

## Product description and its intended use

tretford is constructed from over 70% natural Cashmere goat hair. Ethically sourced through goat-herding communities in Mongolia, it is a unique ribbed construction available in a range of 60 colours. Roll is 2m wide with no fixed length, tile is 500x500mm and rugs are all custom made to size.

### Product identifier (if applicable)

tretford - 60 colours avaliable.

#### Place Manufactured (New Zealand or Overseas)

Overseas, manufactured in Germany

### **Relevant Building Code clauses**

B2 Durability	Performance clause B2.3.1 c) 5 years
C3 Fire Affecting Area beyond the source	Performance clause C3.4 b) - does not apply to detached dwellings, within household units in multi-unit dwellings or outbuildings and ancillary buildings.
F2 Hazardous Building Materials	Performance clause F2.3.1





## Product Review tretford Roll, Tile and Cutom Rugs of

pg 2/4

## Statement of how the building product is expected to contribute to compliance

## B2 Durability - B2.3.1 c)

- tretford has a durability beyond 5 years, based on NZBC b2/VM1 clause 1.1 In-service history.
- Durability supported by a 5-year product warranty.

## C3 Fire Affecting Area Beyond the Source - C3.4 b)

 tretford flooring has been tested to EN ISO 9239.1 - 2010 Flux) mean 7.6 kW/m2. Refer to APL Test Report 161486NZ dated 4 August 2016.

## F2 Hazardous Building Materials - F2.3.1

tretford carpet is certified Global GreeTag Level A.





## Product Review tretford Roll, Tile and Custom Rugs 05/24

pq 4/4

### Limitations on the use of the building product

Suitable for interior applications only.

#### Design requirements that would support the appropriate use of the building product

• tretford is suitable for all areas requiring a durable, colourful sustainable carpet surface.

## Installation requirements

- Install in accordance with Advance Flooring tretford Installation Instructions.
- Ensure substrate is smooth, dry, clean, and free from contamination. For internal applications ensure substrate does not vary from required level by no more than 4mm measured under a 4m straight edge.
- Substrate must have a relative humidity of 75% or below.
- · Must be laid with using adhesive specified and recommended Advance Flooring

### Maintenance requirements

- Maintenance to be in accordance with Advance Flooring, guide tretford carpet.
- Regular maintenance vacuum often.

