



SEAFOAM COLLECTION

Technical Specifications

Construction: Multi-level Loop

Fiber: PUREWEAVE™ Nylon

Gauge: 1/12"

Stitches: 13 per inch

Area per carton: 6m²

Traffic Classification: Commercial - Heavy Duty

Average Pile Height: 4.0 ± 0.5 mm

Standard Backing: EcoAce-Bac®

Tile Size: 50 x 50 cm



Pile Weight: 20 OZ/yd²

Total Thickness: 7.5 ± 0.5 mm

Piece per carton: 24 pieces

Anti-microbial: Ultra Fresh (Available)

Installation Methods




**These given methods of installation are considered as classic solutions. However, certain cases and needs may be different, and designs will differ accordingly.

Certifications



Declare.



CE



Certificate Of Declare

[DOWNLOAD](#)

Certificate Of Cradle To Cradle

[DOWNLOAD](#)

Certificate Of SGLS

[DOWNLOAD](#)

Certificate Of EPD

[DOWNLOAD](#)

Certificate Of CRI

[DOWNLOAD](#)

Performance Specifications

| | Test Code | Standard | Test Result |
|-------------------------------|------------------|----------------------------|---------------|
| Flammability Tests | | | |
| Radiant Panel | ASTM E 648 | ≥45 watt/cm ² | Class I |
| Methenamine Pill | ASTM D2859 | 7 out of 8 | 8 |
| Smoke Density | ASTM E 662 | ≤ 450 DMC | ≤ 450 |
| Stability | | | |
| Delamination | ASTM D3936 | ≥ 3.0 lbc/in | No Separation |
| Dimensional Stability | AACHEN | ≤ 0.2% | ≤ 0.2% |
| Tuft Bind | ASTM D1335 | ≥ 8.0 lbs | ≥ 8.0 lbs |
| Anti-Static | | | |
| Static Propensity | AATCC 134 | ≤ 3.5 kV | ≤ 3.5 kV |
| Colour Fastness | | | |
| Light | AATCC 16 E | ≥ 4-5 | 4-5 |
| Rubbing/Crocking | AATCC 165 | ≥ 4-5 | 4-5 |
| Wear Tests | | | |
| Castor Chair | BS EN 985 | r ≥ 2.4 | r = 2.8 |
| Hexapod Drum | ASTM D5252 | ≥ 3-4 | 3 |
| Generic Tests | | | |
| Nylon Carpet with EcoAce-Bac® | GLP No. : 100231 | | Accredited |
| Acoustic-Nylon | BS EN ISO 354 | Absorption Coefficient-NRC | aw =0.15(H) |

Warranty

Lifetime Commercial Limited Warranty [DOWNLOAD](#)

Additional Information

- VOXFLOr uses Ultra-Fresh Antimicrobial system, which is by controlling odour and staining causing bacteria, mold and mildew growth, Ultra-Fresh antimicrobial additives help to keep products fresher, cleaner and more durable.

Additional Files

Installation Guidelines

[DOWNLOAD](#)

Maintenance Guidelines

[DOWNLOAD](#)

