



DATA SHEET

issue 02/17

Nexus - Stainless Steel Entrance System

pg 1/2

Distributor/Manufacturer

Advance Flooring Systems Limited

Trade Name

Nexus

Product Description

Modular stainless steel grate tile system with stainless steel support frame for entrance areas.

Product Benefit

Nexus is engineered to be an attractive bespoke architectural design feature at entranceways. Nexus is resilient to soiling, staining and provide good slip resistance whilst being easy to clean. Nexus withstands heavy rolling loads. Nexus has excellent resistance to a wide range of atmospheric environments and many corrosive media and can be bespoke manufactured to unlimited variables of size and shape.

Area of Application

Nexus is ideal for extreme levels of foot traffic for any commercial application such as shopping centres, transport hubs and tertiary education facilities.

Composition

Nexus is manufactured with a high grade 304 alloy steel in rectangular or mesh style surfaces that are fused to support profiles and framing system.

Dimensions

Tile depth 20.6mm
Tile size 457.2 x 457.2mm or bespoke manufactured to specific requirements.

Appearance

Lineal grid and mesh styles.

Manufacture

Nexus is manufactured using a process that is ISO 14001:2004 compliant for its Environmental Management Systems

Smoke/Fire

Nexus is a non-combustible material therefore exceeds the NZ requirements.

Slip Test

Nexus has been tested and exceeds the AS/NZS 4586: 2004 NZ & AS 4586: 2013 AU requirements.

Advance Flooring Systems Ltd

email: info@advanceflooringsystems.com

www.advanceflooringsystems.com

NZ : **0508 238 262** AU : **1800 459 682**


Advance
FLOORING SYSTEMS



DATA SHEET

issue 02/17

Nexus - Stainless Steel Entrance System

pg 2/2

Durability

Extra Heavy Commercial.

Sustainability

Advance Flooring Systems and the manufacturer are committed to the protection of the environment and all products are manufactured to strict ISO 14001: 2004 standards.

Installation

Nexus Stainless Steel Grates must be installed by a competent and experienced installer, more information on the recommended installation procedures is available on our website www.advanceflooringsystems.com or upon request.

Cleaning and Maintenance

Stainless steel inherently has low maintenance requirements however we recommend occasional brushing to maintain the appearance. Trapped soil and moisture should be removed from the well by removing the grates as required. Should the grates be unusually soiled the grates can be removed, to be washed and dried. More information on the recommended maintenance procedures is available on our website www.advanceflooringsystems.com or upon request.

Warranty

The manufacturer provides a Ten (10) year limited warranty for manufacturing defects.

Note:

Advance Flooring Systems Ltd recommends that Nexus is used in conjunction with an entrance matting systems that offers moisture absorbency to maximize effectiveness.

Advance Flooring Systems Ltd

email: info@advanceflooringsystems.com

www.advanceflooringsystems.com

NZ : **0508 238 262** AU : **1800 459 682**


Advance
FLOORING SYSTEMS