














Specifications

DESCRIPTION	NORM	DATA
Pile Fiber		100% Polyamide (Solution Dyed)
Gauge		1/10 loop pile
Tuft Density	ISO 1763	147 600 Stitches/m ²
Total Pile Mass	ISO 8543	580 g/m ²
Mass of Pile above the Substrate	ISO 8543	330 g/m ²
Thickness of Pile above the Substrate	ISO 1766	3 mm
Surface Pile Density	ISO 8543	0,110 g/cm ³
Total Weight	ISO 8543	4395 g/m ²
Total Thickness	ISO 1765	7,0 mm
Primary Backing		Non-woven primary backing
Backing		Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Tile Size		50x50cm
Tiles per Box		20 = 5m ²
Installation		



Technical Performances

RHO-LRV		 Classification EN 1307 - 33 / Commercial Heavy Luxury Class – LC1				
37 Colors	%	 Classement UPEC NF 262 - U3P3E1C0 (Certificate n° 349T-003.1) Fire rating EN 13501-1: BflS1				
017	6,1%					
018	3,0%					
021	11,0%					
023	7,2%					
025	5,0%					
027	4,2%					
029	3,2%					
032	17,7%					
033	13,3%	Electrostatic prop.  ISO 6356 ≤ 2,0kV ISO 10965 RT ≥ 10 ¹⁰ Ω		Sound Absorption  ISO 11654 αw = 0,15 (H)		
035	10,6%					
045	6,3%					
047	5,1%					
056	10,4%	Dimensional Stability  EN 986 ≤ 0,10%		Color Fastness  EN 105 - B02 7/8		
058	6,8%					
062	16,9%					
074	10,7%					
076	8,8%					
081	22,3%	 N° 0679-CPR-0196 07 EN 14041: 2004		Castor Chair  EN 985 Passed R≥2,4		
082	10,4%					
083	12,6%					
084	8,8%					
086	6,2%					
088	4,4%					
094	4,4%					
096	5,1%					
095	6,1%					
097	3,3%					
101	20,8%					
106	13,3%					
113	7,9%					

TECSOM - 3580 CITY SQUARE



115	6.5%
123	5,5%
124	12,4%
127	5,9%
134	16,7%
135	11,5%
931	24,3%



The above information is subject to modifications for the benefit of further improvement. (Updated on 24/03/2017)

Advance Flooring Systems Ltd
email: info@advanceflooringsystems.com
www.advanceflooringsystems.com

Call us: **0508 238 262**

