
















**Specifications**

DESCRIPTION	NORM	DATA
Pile Fiber		100% Polyamide (Solution Dyed)
Gauge		5/64e loop pile
Tuft Density	ISO 1763	223 600 Stitches/m <sup>2</sup>
Total Pile Mass	ISO 8543	850 g/m <sup>2</sup>
Mass of Pile above the Substrate	ISO 8543	520 g/m <sup>2</sup>
Thickness of Pile above the Substrate	ISO 1766	3,5 mm
Surface Pile Density	ISO 8543	0,149 g/cm <sup>3</sup>
Total Weight	ISO 8543	4800 g/m <sup>2</sup>
Total Thickness	ISO 1765	7,5 mm
Primary Backing		Non-woven primary backing
Backing		Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Tile Size		50x50cm
Tiles per Box		20 = 5m <sup>2</sup>
Installation		



Technical Performances

RHO-LRV		 Classification EN 1307 - 33 / Commercial Heavy Luxury Class – LC2			
9 Colors	%	Fire rating EN 13501-1: BflS1 			
130	23.7%				
139	16.6%				
140	14.0%				
144	6.0%	<b>Heated Floor</b>  ISO 10456    0,10 m² K/W	<b>Impact Noise Reduction</b>  EN ISO 10143-3    ΔL (w) 25 dB		
171	26.1%	<b>Electrostatic prop.</b>  ISO 6356    ≤ 2,0kV ISO 10965    RT ≥ 10 <sup>10</sup> Ω			
201	26.3%				
230	21.6%	<b>Dimensional Stability</b>  EN 986    ≤ 0,10%		<b>Sound Absorption</b>  ISO 11654    α <sub>w</sub> = 0,20 (H)	
239	9.6%	<b>Color Fastness</b>  EN 105 - B02    7/8			
511	4.6%				
		 N° 0679-CPR-0196 07 EN 14041: 2004	<b>Castor Chair</b>  EN 985    Passed R≥2,4		



The above information is subject to modifications for the benefit of further improvement. (Updated on 01/09/2017)