



DATA SHEET

Spacewalk - Carpet Planks

issue 02/17

pg1/2

Distributor/Manufacturer

Advance Flooring Systems Limited/Voxflor

Trade Name

Spacewalk 100 / 200 / 300 series

Product Description

Solution Dyed Nylon 6 fibre carpet planks with a PVC backing system.

Product Benefit

Long lasting tufted carpet tile designed for mix and match flexibility, ease of installation and easy to clean.

Area of Application

Spacewalk 100 / 200 / 300 series is suitable for use in any high traffic commercial areas.

Composition

Spacewalk 100 / 200 / 300 series carpet planks are made with a graphic tufted construction consisting of 100% solution dyed nylon, bonded to a fiberglass reinforced PVC backing system.

Dimensions

Pile height	4mm \pm 0.5mm at 20 OZ/yd ² / 4.5mm \pm 0.5mm at 23 OZ/yd ² / 5.0mm \pm 0.5mm at 28 OZ/yd ²
Plank size	250 x 1000mm

Pattern & Colours

Graphic tufted natural pattern available in a range of 5 colours.

Manufacture

The Spacewalk series of carpet planks are manufactured in China, by Voxflor using a manufacturing process that is ISO 14001:2004 compliant for its Environmental Management Systems.

Smoke/Fire

Spacewalk carpet planks have been tested and comply by exceeding the NZ requirements

Electrical Resistance

Spacewalk carpet planks have been tested and comply by exceeding the NZ requirements

Durability

Heavy Commercial



DATA SHEET

Spacewalk - Carpet Planks

issue 10/16

pg 2/2

Sound Absorption

Voxflor carpet tiles can reduce reverberative noise in a commercial office environment.

UV Resistance

Some fading may be observed in areas of intense sunlight.


Sustainability

Voxflor is committed to the protection of the environment and all products are manufactured to strict ISO 14001: 2004 standards.


Installation

Spacewalk carpet planks must be installed by a competent and experienced carpet installer and we recommend the full stick method - more information on the recommended installation procedures is available on our website www.advanc flooring systems.com or upon request.


We recommend the following installation method for Spacewalk carpet planks.



HERRINGBONE



ASHLAR



CHECKERBOARD

Recommended Adhesive

Strongbond 65 – Look Floors, or Polymer 999 PS – Gilt Edge Industries.

Cleaning and Maintenance

Proper maintenance is one of the most important factors to ensure good performance of carpet. When possible Spacewalk should be vacuumed daily. In the first instance, a good entrance matting system installed at entry areas will help collect up to 90% soiling before it is tracked into the interior of the building - more information on the recommended maintenance procedures is available on our website www.advanc flooring systems.com or upon request.

Warranty

The manufacturer warrants and backs the product with a 15 year Abrasive Wear, 15 year Delamination limited warranties and a lifetime Anti-Static limited warranty.

Advance Flooring Systems Ltd

email: info@advanc flooring systems.com

www.advanc flooring systems.com

Call us: **0508 238 262**


Advance
FLOORING SYSTEMS