BLOQ CARPET TILES - SPECIFICATION TEXT



1. GENERAL INFORMATION

MANUFACTURER BLOQ creative carpet tiles

PRODUCT NAME Rhythm

2. PRODUCT DESCRIPTION

The carpet tile is GUT certified and conforms to the EN 1307 classification. The carpet tile is suitable for intensive use and is therefore suitable for wheelchairs.

The pile weight of the carpet tile is approximately 540 g/m2. The carpet tile is stabilised by a bitumen backing, the finish of which consists of modified bitumen with the addition of thermoplastic elastomers. The backing contains at least 70% recycled material. The carpet tile also has a glass fibre fleece that gives better dimensional stability ($\le 0.2\%$).

The pile material consists of 100% polyamide fibre type 6 from Aquafil and is Solution Dyed. This type of yarn means better colour fastness and the best result against light and water.

The carpet tile has a tufted loop pile with a striped pattern.

The collection consists of 8 colours.

The production and finishing of this carpet tile takes place in the Netherlands by an ISO 9001 certified manufacturer.

3. TECHNICAL SPECIFICATIONS

TYPE OF MANUFACTURE Tufted loop pile with pattern 1/10"

PILE FIBER COMPOSITION 100% Polyamide 6 Solution Dyed

Nylon from Aquafil

BACKING Bitback, modified bitumen –

70% recycled content.

DIMENSION 50 X 50 cm

 $\begin{array}{ll} \textbf{PILE WEIGHT} & 540 \text{ g/m}^2 \end{array}$

TOTAL WEIGHT 4 250 g/m²

TOTAL THICKNESS 6,0 mm

CLASSIFICATION Class 33 – EN 1307

CASTOR CHAIR RATING EN 985 | A: intensive use

FIRE CLASSIFICATION EN 13501-1 | $B_n - s1$

IMPACT SOUND INSULATION EN ISO 10140-3 | ΔL_{w} 25 dB

PERMANENT ANTISTATIC ISO 6365 I ≤ 2 kV

THERMAL RESISTANCE ISO $10965 \mid \le 1 \times 10^9 \text{ Ohm}$

COLOUR FASTNESS TO LIGHT EN ISO 105-B02 | ≥ 7

4. CERTIFICATES

WARRENTY 15 years

INTERPORT

The product fulfils the GUT criteria. The GUT licence number is: 0D32FA3E.

Only textile floor coverings that have been tested by recognized European research institutes for harmful substances, emissions and odour formation are given a licence number.