

# Technical Data Sheet

## ExtraTread - 1/23 Entrance System



### Manufacturer/Distributor

Advance Flooring Systems Limited

### Trade Name

ExtraTread

### Product Description

An ultra-low 10mm deep aluminium strip mat system with polyamide inserts for entrance areas.

### Product Benefit

ExtraTread is an entrance mat system engineered to trap soiling and 37% more moisture absorption compare to other aluminium strip mat systems, that is easy to clean and protects flooring surfaces inside. ExtraTread has a heel-proof fully interlocking aluminium base that eliminates dirt drop through by specially designed dirt collection rails.

### Area of Application

ExtraTread is ideal for extreme levels of foot traffic for any commercial entry application such as public space, transport hubs and commercial premises. ExtraTread is to be used indoors or in weather protected areas.

### Composition

ExtraTread is manufactured with continuous anodised aluminium interlocking strips, molded anti-clatter feet and polyamide carpet inserts.

### Dimensions

Strip depth	10mm
Overall tread size	81mm

### Appearance

Natural anodised aluminium interlocking strip system available in a range of 8 polyamide insert colours.

### Manufacture

ExtraTread is manufactured by Advance Flooring systems to its copyright design.

### Smoke/Fire

The ExtraTread matting system has been tested and exceeds the AU & NZ requirements.

# Technical Data Sheet

## ExtraTread - 1/23

### Entrance System



#### Slip Test

ExtraTread has been tested and exceeds the AS/NZS 4586: 2004 NZ & AS 4586: 2013 AU requirements.

#### Durability

Extra Heavy Commercial.

#### UV Resistance

Some fading of the polyamide carpet inserts may be observed in areas of intense sunlight. Aluminium sections are not affected.

#### Sustainability

Advance Flooring Systems is committed to the protection of the environment. ExtraTread is designed to minimise environmental impacts during manufacture and engineered to last a long first lifecycle supported by a 15 year warranty.

#### Installation

ExtraTread tiles must be installed by a competent and experienced installer, more information on the recommended installation procedures is available on our website [www.advanceflooring.co.nz](http://www.advanceflooring.co.nz) or upon request.

#### Cleaning and Maintenance

ExtraTread has low maintenance requirements and does not have to be removed for cleaning as dirt cannot drop through. Special dirt collection zones and polyamide infills gather dirt for simple and effective cleaning.

Daily Maintenance: Vacuum ExtraTread thoroughly with a powerful vacuum cleaner preferably with power driven brushes. This agitates the pile to loosen the trapped dirt.

Periodic Maintenance: A routine visual inspection will identify when ExtraTread is becoming embedded with dirt which can be removed by a water spray extraction method. Alternatively, ExtraTread can be scrubbed by machine or hand, rinse thoroughly using a wet and dry vacuum

cleaner. In cases of staining, household solvents may be used, however must only be applied to a rag and rubbed onto the pile. Do not pour solvents directly onto the mat as a breakdown of the infill adhesive may result.

More information on the recommended maintenance procedures is available on our website [www.advanceflooring.co.nz](http://www.advanceflooring.co.nz) or upon request.

#### Warranty

Advance Flooring Systems provides a fifteen (15) year product warranty, that the product will be free of manufacturing defects and the product is maintained according to the manufacturers maintenance instructions, subject to fair wear and tear. Replacement parts are also available for the warranty period.