# **Technical Data Sheet**



# Gecko - 1/23

# **Entrance Carpet Tiles**

# Manufacturer/Distributor

Advance Flooring Systems Limited/Voxflor

# Trade Name

Gecko

### **Product Description**

Solution Dyed Nylon 6 carpet tiles with a recycled backing system. Declare Certified.

# **Product Benefit**

Gecko is a sustainably manufactured entrance carpet tile with thick denier fibres designed to trap soil from any direction, that is durable and easy to clean.

# Area of Application

Gecko is suitable for building entrances and for use in any high traffic commercial areas.

### Composition

Gecko carpet tiles are made with a tufted loop pile construction consisting of 100% Universal nylon 6 bonded to Declare Certified Comfort Back or EcoBac backing system.

# Dimensions

Overall thickness6.6mm (EcoBac), 10mm (Comfort-Backing or EcoBac)Tile size500 x 500mm

# Pattern & Colours

Tufted level loop appearance available in 1 colour

# Manufacture

Gecko carpet tiles are manufactured in China, by Voxflor using manufacturing processes that are ISO 14001:2004 compliant for its Environmental Management Systems.

# Smoke/Fire

Gecko entrance carpet tiles have been tested and exceed the NZ requirements.



# **Technical Data Sheet**



# Gecko - 1/23 Entrance Carpet Tiles

# Antistatic

Gecko entrance carpet tiles have been tested to have an electrostatic resistance.

# Durability

Class 33, Heavy Commercial

# **Sound Absorption**

Gecko carpet tiles can reduce impact noise by up to 21 dB.

# **UV Resistance**

Some fading may be observed in areas of intense sunlight.

# **Sustainability**

Voxflor is committed to the protection of the environment and all products are manufactured to strict ISO 14001: 2004 standards.

### Installation

Gecko carpet tiles must be installed by a competent and experienced carpet installer and we recommend the full stick method - more information on the recommended installation procedures is available on our website <u>www.advanceflooring.co.nz</u> or upon request.

We recommend the following installation method for Gecko.

# **Recommended Adhesives**

Entrance matting applications - Giltgrip 88 – Gilt Edge Industries Ltd Applications other than entrance matting - Strongbond 65 – Look Floors, or Polymer 999 PS – Gilt Edge Industries Ltd.

# **Cleaning and Maintenance**

Proper maintenance is one of the most important factors to ensure good performance of any carpet.

Gecko should be vacuumed daily as it will collect up to 90% soiling before it is tracked into the interior of the building. More information on the recommended maintenance procedures is

# Warranty

The manufacturer provides a 10-year limited warranty.

